

UL3122 silicone rubber wire

Technical Parameters:

Rated Temperature:200°C

Rated voltage:300Vac

Conductor:tinned copper

Standard:UL758



Use:Used for heating equipment, industrial machinery, ovens, household appliances, lighting systems, electrical control cabinets, and other applications requiring dependable high-temperature wiring.

Color:white,black,red,yellow,blue,green,brown

Conductor		Insulation(mm)	Outer diameter	Conductor Resistance	
Size(AWG)	Standing (No/ ¢ mm)		(mm)	(20 ⁰ C Ω/km)	
26	1/0.40	0.60	1.60	143	
	7/0.16		1.68	150	
24	1/0.51		1.71	84.2	
	7/0.20		1.81	88.9	
22	1/0.65		1.85	53.2	
	7/0.254		1.97	57.8	
20	1/0.81		2.01	35.2	
	7/0.31		2.14	37.6	
	26/0.16		2.14	37.6	
18	1/0.2		2.22	22.2	
	7/0.39		2.39	23.2	
	41/0.16		2.39	23.2	
16	1/0.30		2.5	14	
	7/0.49		2.69	14.6	
	26/0.254		2.69	14.6	

We can offer customised services according to your requirements.

Jiangsu XingYuan High Temperature Wire & Cable Co.,Ltd

www.xingyuancable.com Mobile/WhatsApp/WeChat:+86 18361138773 Email:xycable@foxmail.com